USA 20-25/25 automatic buried clamp 12440

CE 2/2024

Areas of application:

For the simple plaster laying of flexible pipes on plasterboard and concrete.

Installation Guide:

- Drill a 6 mm Ø hole
- Insert the USA in the drill-hole
- Insert flexible or rigid pipe into the USA and push down until it closes automatically

Product details:

Colour	light grey
Content pack/box	100 / 2.200
Clamping range Pipe dimension	20-25
Dowel length in mm	25

Mounting and usage instructions:

The USA automatically closes around the laid pipe. This clip is available in four ranges, but all are suitable for holding two pipe dimensions. For example the USA 20-25 can hold both a size 20 or a size 25 pipe. The USA can easily be opened without a tool.

Product benefits/properties:

USA is a buried clamp for flexible pipes and tubes. For flush surface mounting. Saves you time!

Technical data:

Material	PP Temperature range: -10 °C up to +85 °C silicon-free LSFOH halogen-free low-smoke tested according to OVE guideline R14
Weight per piece	2,70 g
Max. reccd. load	Reference value: USA 20-25/25: 96.56 N concrete, 84.08 N solid brick, 93.88 N hollow brick, 42.64 N aerated Concrete, 76.48 N plasterboard
Breaking load	Reference value: USA 20-25/25: 241.40 N (24 kg) concrete, 210.20 N (21 kg) solid brick, 234.70 N (23 kg) hollow brick, 106 N (10 kg) aerated concrete, 191 N (19 kg) plasterboard
GTIN (EAN)	9 008439 224401



An innovative product for sub-plaster mounting - the Buried Clamp Automatic USA. A quick push is enough to affix the clamp to the pipe.

Schnabl®
time saving products

Only the ORIGINAL is ingenious

Schnabl Stecktechnik GmbH, Bahnhofplatz 1, po box 63, 3100 St. Pölten, Austria
Telephone +43 2742 22167-0, office@schnabl.works, www.schnabl.works

ISO 9001:2008 TÜV AUSTRIA