

# DKS 6-20 Dowel clamp 30030

CE

## Areas of application:

For the single installation of casing pipes (single cable and cable bundles) such as antenna cables, telephone lines and flex s.

## Installation Guide:

- Drill a 6mm Ø hole
- Wrap the DKS around the cable
- Insert the DKS into the drill hole

## Product details:

Colour:	light grey
Content pack/box	200 / 4.800
Clamping range in	6-20

## Mounting and usage instructions:

Cover the cable(s) with the DKS and insert the DKS into a 6 mm drill hole. Drill. Fasten. Done!

## Product benefits/properties:

Good cable tension options with the DKS. When laid, the strap is barely visible.

## Technical data:

Material	PP, UV stabilised Temperature range: -10 °C up to +85 °C silicon-free <b>halogen-free</b>
Weight per piece	0,70 g
Max. reccd. load	Reference value: DKS 3-13: 170 N (17 kg) concrete, 180 N (18 kg) solid brick
Breaking load	Reference value: DKS 3-13: 248.00 N (24.8 kg) concrete, 271.80 N (27 kg) hollow brick

GTIN (EAN)



Schnabl Stecktechnik GmbH  
Bahnhofplatz 1, Postfach 63, 3100 St. Pölten, Austria  
Telefon +43(0)2742/22167-0, Telefax +43(0)2742/22167-50  
office@schnabl.works, www.schnabl.works

Stand: 2/2020

 **Schnabl**<sup>®</sup>  
time saving products