

DSN 50 Dowel fastening nail 30360



Areas of application:

Conduit installations: Affixing cable ducts, for smoke detectors and small lamps with the DSN.

Installation Guide:

- Drill a 6 mm Ø hole
- Put Dowel Fastening Nail through a hole of the item to be fixed and push the DSN into the drill-hole.

Product details:

Colour:	light grey
Content pack/box	200 / 6.000
Nail length in mm	49

Product benefits/properties:

Very good clamping effect thanks to nail head's special shape. No dowels or screws required. All products are for 01 - 20 mm material thickness suitable for E0 cables.

Technical data:

Material	PA 6, UV stabilised Temperature range: -20 °C up to +85 °C silicon-free halogen-free
Weight per piece	1,00 g
Max. recd. load	Reference value: DSN30: 200 N (20 kg) concrete, 200 N (20 kg) solid brick, 150 N (15 kg) hollow brick, 50 N (5 kg) aerated concrete, 70 N (7 kg) plasterboard 25 mm
Breaking load	Reference value: DSN30: 340 N (34 kg) concrete, 330 N (33 kg) solid brick, 310 N (31 kg) hollow brick, 75 N (7.5 kg) aerated concrete, 85 N (8.5 kg) plasterboard 25 mm
GTIN (EAN)	9 008439 303601



With the DSN 30 und DSN 40 you will successfully fasten fire detectors, lamps and sockets at the push of a thumb.

Schnabl Stecktechnik GmbH
Bahnhofplatz 1, Postfach 63, 3100 St. Pölten, Austria
Telefon +43(0)2742/22167-0, Telefax +43(0)2742/22167-50
office@schnabl.works, www.schnabl.works

 **Schnabl**[®]
time saving products

Stand: 2/2020