

KB 10 Cable bracket 30420

CE

Areas of application:

For the conduit laying of non-metallic sheathed cables. The KB 11 cable bracket can hold up to 10 cables (3 x 1.5 mm²).

Installation Guide:

- Drill a 6 mm Ø hole
- Insert the KB into the drill-hole
- Insert the cable/s into the gap between the wall and ceiling.
- If required up to two EC clamps, in any pipe diameter size can be attached directly to the KB

Product details:

Colour:	light grey
Content pack/box	50 / 1.000
Clamping range in	100

Product benefits/properties:

Perfect and quick laying of multiple cables directly on the ceiling. Insert the KB with minimal effort, then lay the cable. The KBs own internal stress is sufficient to ensure the cable is mounted firmly even against high temperature fluctuations. Unique attachment option for the EC Euro Clip - for retrofitting of a pipe or the separate laying of different cables - without the need for drilling.

Technical data:

Material	PP, UV stabilised Temperature range: -10 °C up to +85 °C silicon-free halogen-free
Weight per piece	6,70 g
Max. recd. load	240 N (25 kg) concrete, 230 N (23 kg) solid brick
Breaking load	343.70 N (34 kg) concrete, 331 N (33 kg) solid brick
GTIN (EAN)	9 008439 304202



The KB cable brackets have been developed for the section installation of wiring harnesses.

Schnabl Stecktechnik GmbH
Bahnhofplatz 1, Postfach 63, 3100 St. Pölten, Austria
Telefon +43(0)2742/22167-0, Telefax +43(0)2742/22167-50
office@schnabl.works, www.schnabl.works

 **Schnabl**[®]
time saving products

Stand: 2/2020