

# KB 13 Cable bracket 30430

CE

## Areas of application:

For the conduit laying of non-metallic sheathed cables. The KB 13 cable bracket can hold up to 13 cables (3 x 1.5 mm<sup>2</sup>).

## Installation Guide:

- Drill a 6 mm Ø hole
- Insert the KB into the drill-hole
- Insert the cable/s into the gap between the wall and ceiling.
- If required up to two EC clamps, in any pipe diameter size can be attached directly to the KB

## Product details:

Colour:	light grey
Content pack/box	100 / -
Clamping range in	100

## Product benefits/properties:

Perfect and quick laying of multiple cables directly on the ceiling. Insert the KB with minimal effort, then lay the cable. The KBs own internal stress is sufficient to ensure the cable is mounted firmly even against high temperature fluctuations. Unique attachment option for the EC Euro Clip - for retrofitting of a pipe or the separate laying of different cables - without the need for drilling.

## Technical data:

Material	PP, UV stabilised Temperature range: -10 °C up to +85 °C silicon-free <b>halogen-free</b>
Weight per piece	7,00 g
Max. recd. load	240 N (25 kg) concrete, 230 N (23 kg) solid brick
Breaking load	343.70 N (34 kg) concrete, 331 N (33 kg) solid brick
GTIN (EAN)	9 008439 304301



The KB cable brackets have been developed for the section installation of wiring harnesses.

Schnabl Stecktechnik GmbH  
Bahnhofplatz 1, Postfach 63, 3100 St. Pölten, Austria  
Telefon +43(0)2742/22167-0, Telefax +43(0)2742/22167-50  
office@schnabl.works, www.schnabl.works

 **Schnabl**<sup>®</sup>  
time saving products

Stand: 2/2020