

TA 30/55 Support anchor 33150

CE

Areas of application:

For the chased fixing of sheathed cables, flexible tubing and conduits, on and under plasterboard.

Installation Guide:

- Drill a 6mm Ø hole
- Insert the TA in the drill-hole
- Click the TB onto the TA
- Put flexible pipes under the TB
- Push the TB tight with your thumb
- Cut the end points of the TB to the desired size

Product details:

| | |
|--------------------|-------------|
| Colour: | light grey |
| Content pack/box | 100 / 3.000 |
| Shaft length in mm | 30 |
| Dowel length in mm | 55 |

Mounting and usage instructions:

The TB is fixed to the TA support anchor. Several TBs can be fixed to one TA. The fixing of the TBs can be done in several stages.

Product benefits/properties:

The TB provides a secure hold even with different conduits/cables dimensions. Fast cable placement with no plastering.

Technical data:

| | |
|------------------|--|
| Material | PA 6, UV stabilised Temperature range: -20 °C up to +85 °C silicon-free halogen-free |
| Weight per piece | 2,00 g |
| Max. recd. load | for TA 100/25: 260 N (26 kg) concrete, full brick, 250 N (25 kg) hollow brick, 100 N (10 kg) aerated concrete |
| Breaking load | TA 100/25: 369 N (36.9 kg) concrete, 374 N (37 kg) hollow brick, 365.2 N (36.5) full brick, 148.1 N (14.8 kg) aerated concrete |

GTIN (EAN)



With the TA in two sizes, Schnabl has in combination with the TB a system for all requirements - on or under plasterboard



Schnabl Stecktechnik GmbH
Bahnhofplatz 1, Postfach 63, 3100 St. Pölten, Austria
Telefon +43(0)2742/22167-0, Telefax +43(0)2742/22167-50
office@schnabl.works, www.schnabl.works

 **Schnabl**[®]
time saving products

Stand: 2/2020