

# USA 25-32/25 automatic buried clamp

## 12450



### Areas of application:

For the simple plaster laying of flexible pipes on plasterboard and concrete.

### Installation Guide:

- Drill a 6 mm Ø hole
- Insert the USA in the drill-hole
- Insert flexible or rigid pipe into the USA and push down until it closes automatically

### Product details:

Colour:	light grey
Content pack/box	100 / 1.200
Clamping range Pipe	25-32
Dowel length in mm	25



### Mounting and usage instructions:

The USA automatically closes around the laid pipe. This clip is available in four ranges, but all are suitable for holding two pipe dimensions. For example the USA 20-25 can hold both a size 20 or a size 25 pipe. The USA can easily be opened without a tool.


### Product benefits/properties:

USA is a buried clamp for flexible pipes and tubes. For flush surface mounting. Saves you time!

### Technical data:

Material	PP, UV stabilised Temperature range: -10 °C up to +85 °C silicon-free <b>halogen-free</b>
Weight per piece	4,80 g
Max. recd. load	Reference value: USA 20-25/25: 170 N (17 kg) concrete, 150 N (15 kg) solid brick, 160 N (16 kg) hollow brick, 75 N (7.5 kg) aerated Concrete, 130 N (13 kg) plasterboard
Breaking load	Reference value: USA 20-25/25: 241.40 N (24 kg) concrete, 210.20 N (21 kg) solid brick, 234.70 N (23 kg) hollow brick, 106 N (10 kg) aerated concrete, 191 N (19 kg) plasterboard

GTIN (EAN)



*An innovative product for sub-plaster mounting - the Buried Clamp Automatic USA. A quick push is enough to affix the clamp to the pipe.*



Schnabl Stecktechnik GmbH  
Bahnhofplatz 1, Postfach 63, 3100 St. Pölten, Austria  
Telefon +43(0)2742/22167-0, Telefax +43(0)2742/22167-50  
office@schnabl.works, www.schnabl.works

 **Schnabl**<sup>®</sup>  
time saving products

Stand: 2/2020